

NOTEBY 1966  
1950

NO BS-3

326N

Pröveserie II Terrh. = 73.9m

| Dyp<br>m | W    | V    | F  | H <sub>1</sub> | H <sub>3</sub> | K   | O   | pH   | γ    | Merknad                    |
|----------|------|------|----|----------------|----------------|-----|-----|------|------|----------------------------|
| 1.0      | 22.8 | 38.6 |    |                | 1750           |     | 0.9 |      | 2.09 | Törrskorpelåire            |
| 2.0      | 26.1 | 41.1 | 46 | 234            | 1750 (137)     | 1.0 | 7.0 | 2.03 |      | Törrskorpelåire            |
| 3.0      | 28.8 | 44.6 | 47 | 136            | 526            | 7.4 | 1.0 | 7.2  | 1.99 | Törrskorpelåire            |
| 4.0      | 31.2 | 46.3 | 42 | 46             | 172            | 4.0 | 0.9 | 7.5  | 1.96 | Leire m/ en rusten rötgång |
| 5.0      | 36.5 | 50.4 | 45 | 29             | 172            | 4.0 | 0.9 | 8.0  | 1.89 | Leire, homogen             |
| 6.0      | 35.8 | 49.5 | 35 | 9              | 149            | 3.5 | 0   | 8.0  | 1.88 | Leire m/sandkorn           |
| 7.0      | 39.5 | 57.9 | 41 | 12             | 144            | 3.5 | 0   |      | 1.83 | Leire m/sandkorn           |
| 8.0      | 37.9 | 51.0 | 39 | 11             | 104            | 2.6 | 0   | 8.3  | 1.95 | Leire m/sandkorn           |