

N O T E B Y

787

Seilduksgaten 25 b

(tilfluktsrum)

NO: D3 III

ang. sk  
✱

overført 80

II  $\odot$   $\frac{23.99}{-12.01}$  36.0  
314N

I  $\odot$   $\frac{26.13}{-7.37}$  33.5  
313N

M: 1:200

1  $\frac{25.76}{-2.74}$  28.5

25

27

Seilduksgaten

V = vanninnhold i volumprosent;  
F = relativ finhet.

Dyp i m	V	F	H <sub>1</sub>	H <sub>3</sub>	O	K	Anm
1.5	30.4			700		8.5	Tørrskorpeleire
2.0	30.2			1140		10.7	"
2.5	38.5	30	110.5	760		8.8	"
3.0	38.6	30	70.0	389		6.3	"
4.0	44.6	32	17.8	140		3.4	Leire
5.0	46.8	34	15.4	132		3.2	"
6.0	48.6	36	14.1	124		3.1	"
7.0	49.3	38	17.4	168		3.9	"
8.0	45.8	33	15.8	184		4.2	"
9.0	49.4	38	18.2	132		3.2	"
10.0	44.5	32	20.7	127		3.1	"
11.0	46.2	36	25.9	140		3.4	"
12.0	45.2	33	22.8	140		3.4	"

Serie II

Dyp i m	V	F	H <sub>1</sub>	H <sub>3</sub>	O	K	Anm.
1.5	37.3	30	107.5	330		5.8	Tørrskorpeleire
2.0	38.2	30	87.5	563		7.6	"
2.5	44.4	35	36.5	253		5.1	Leire
3.0	42.3	32	30.4	313		5.7	"
4.0	45.2	35	25.9	153		3.6	Tørrskorpeleire
5.0	48.4	38	19.7	158		3.7	Leire
6.0	50.0	41	18.2	120		3.0	"
7.0	50.0	39	15.4	100		2.6	"
8.0	48.2	39	23.5	120		3.0	"
9.0	48.4	38	21.4	107		2.7	"
10.0	51.0	43	18.7	104		2.6	"
11.0	50.4	41	17.8	98		2.5	"
12.0	50.2	42	19.7	120		3.0	"

Betegnelse

Seilduksgt. 25 b

⊙ Prøveserie

⬇ Terr.kote Dyp i m. til fjell  
⬇ Fjellkote

787

NORSK TEKNISK BYGGEKONTROLL

Lab. nr. 515-765-1941

D 3 III