

Prøveserie	Nr.	Dybde m	Vanninnhold %	Omrørt konusverdi t/m ²
M	1	0,2	26,0	
	2	1,0	21,7	
	3	2,0	21,5	
	4	3,0	22,8	
	5	4,0	26,3	3,7
	6	5,0	26,5	1,1
	7	6,0	26,3	2,9

Antatt overgang, dybde 6,0 m, kote 115,0.

Prøveserie	Nr.	Dybde m	Vanninnhold %	Omrørt konusverdi t/m ²
N	1	0,2	51,6	
	2	1,0	24,7	
	3	2,0	24,4	
	4	3,0	25,3	3,9
	5	4,0	26,9	2,3
	6	5,0	32,2	0,33
	7	6,0	38,2	

Antatt overgang, dybde 4,0 m, kote 114,0.

Prøveserie	Nr.	Dybde m	Vanninnhold %	Omrørt konusverdi t/m ²
O	1	0,2	37,9	
	2	1,0	20,5	
	3	2,0	23,6	8,4
	4	3,0	26,6	3,0
	5	4,0	30,2	1,3
	6	5,0	30,5	0,34
	7	6,0	32,4	

Antatt overgang, dybde 4,0 m, kote 113,5.

Prøveserie	Nr.	Dybde m	Vanninnhold %	Omrørt konusverdi t/m ²
P	1	0,2	42,3	
	2	1,0	25,6	
	3	2,0	25,0	
	4	3,0	26,5	4,5
	5	4,0	26,8	2,7
	6	5,0	33,8	0,33
	7	6,0	34,7	

Antatt overgang, dybde 4,0 m, kote 113,0.