

50 61^{III}

308H-309H

B11

Arbeid nr. 6/54 NORSK ELEKTRISK KABELFABRIKK. Hote BRYN.	Sonderbor.		Dybde, m.	Opptatte prøver Jordart.	Naturlig vanninnhold-W		pH	Skjærfasthet i t/m	Sensitivitet
	Belastn. kg	Antall 1/2 omdreining			W _L - flytegrense	W _p - utrullingsgrense			
308H Pr IV (1954)	1		1	Skorpelleire, mjelig, oksydet	35	18	6.7	1	5
	2		2	" " " "	30	19	7.0	2	10
	3		3	Leire m/brune stølper	25	20	7.0	3	
	4		4	" " " ensartet.	20	21	7.3	4	
	5		5	" " " "	18			5	
	6		6	" " " "	15			6	
	7		7	" " " "	12			7	
	8		8	" " " "	10		7.7	8	
	9		9	" " " "	8			9	
309H Pr V (1954)	1		1	Skorpelleire, oksydet	35	18	6.0	1	5
	2		2	" " " "	30	19	6.2	2	10
	3		3	" " " "	25	20	6.4	3	
	4		4	Leire, fast.	20	21	6.9	4	
	5		5	" " " "	18		7.1	5	
	6		6	" " " ujevn, faste stølper	15			6	
	7		7	" " " "	12			7	